PRASEK®
PREMIUM
PRECISIÓN ASEGURADA



The PR-380 light meter measure light intensity and display results in Lux or FC. It has a high sampling rate of 100/s. UT380 series low power consumption allows up to 200 hours of continuous operation. Results can be stored within the device and transfered to PC for further analysis, printing and storage.

SPECIFICATIONS

	Range	PR-382
Illuminance measurement (Lux)	20 Lux	±(3%+20)
	200 Lux	±(3%+8)
	2000 Lux	±(3%+8)
	20000 Lux	±(3%+8)
Illuminance measurement (Fc)	2 Fc	√
	20 Fc	√
	200 Fc	√
	2000 Fc	√
Features		
Display count		2000
Auto range		√
Data hold		√
Auto power off	Around 10 minutes	√
Low battery indication	Around ≤7.1V	√
MAX/MIN mode		√
Data storage		2044
USB interface		√
Auto record time setup		√
Real-time clock		√



● PR-382

GENERAL CHARACTERISTICS

Power	9V battery (6LF22)
Display	22.5mm x 32.5mm
Product color	Red and grey
Product net weight	185g
Product size	195mm x 45mm x 26mm
Standard accessories	Carrying bag, USB interface cable (UT382) , PC software CD (UT382)
Standard individual packing	Blister, gift box, English manual
Standard quantity per carton	20pcs
Standard carton measurement	447mm x 300mm x 335mm
Standard carton gross weight	7kg